



(19)

(11) Publication number:

0'

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **06032068**(51) Intl. Cl.: **H01P 5/22**(22) Application date: **04.02.94**

<p>(30) Priority:</p> <p>(43) Date of application publication: 18.08.95</p> <p>(84) Designated contracting states:</p>	<p>(71) Applicant: NIPPON ANTENNA CO</p> <p>(72) Inventor: WATABE TAKASHI</p> <p>(74) Representative:</p>
---	---

(54) HYBRID RING CIRCUIT

(57) Abstract:

PURPOSE: To obtain a hybrid ring circuit made up of a line having a width of one kind.

CONSTITUTION: A line 7(8) whose impedance is about Z_c and whose phase angle is nearly θ_2 is connected between terminals P1 and P2 (terminals P3 and P4) and a line 5(6) whose impedance is about Z_c and whose phase angle is nearly θ_1 is connected between the terminals P1 and P4 (terminals P2 and P34). The width of the four lines 5, 6, 7, 8 is all selected to be W. The phase angle θ_2 is equal to $(180^\circ - \theta_1)$, and then a total circulating phase angle of the hybrid ring circuit is 360° .

COPYRIGHT: (C)1995,JPO

